

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claims 13 and 25, and AMEND claims 1, 5, 12 and 14-16 in accordance with the following:

1. (currently amended) A transporting apparatus, comprising:
a supporting part;
first and second driving axles rotatably supported by the supporting part;
a plurality of driving links respectively combined to the first and second driving axles;
a plurality of transporting links rotatably connected to the driving links; ~~and~~
a transporting table rotatably connected to the transporting links by pivots to reciprocate by a cooperation of the driving links and the transporting links, the first and second driving axles being aligned in a reciprocating direction of the transporting table; and
a driving part to drive the first and second driving axles, the driving part including,
a first motor, wherein the first motor drives the first and second driving axles to
rotate;
a second motor, wherein the second motor drives a supporting shaft of the
supporting part which is interlocked with the first and second driving axles to rotate; and
a third motor, wherein the third motor drives the supporting shaft and the second
motor to move up and down,
wherein the first driving axle is passed through a center of the supporting part, and the second driving axle is eccentrically passed through the supporting part ~~behind~~along an axis
formed by the first driving axle inand the reciprocating direction of the transporting table.

2. (cancelled)

3. (original) The transporting apparatus according to claim 1, wherein the pivots connecting the transporting links with the transporting table are aligned in the reciprocating direction of the transporting table.

4. (original) The transporting apparatus according to claim 1, further comprising:
an engaging device to interlock the first driving axle with the second driving axle, so that the first and second driving axles are rotated reversely to each other.

5. (currently amended) The transporting apparatus according to claim ~~2~~1, further comprising:
an engaging device to interlock the first driving axle with the second driving axle, so that the first and second driving axles are rotated reversely to each other.

6. (original) The transporting apparatus according to claim 1, wherein the driving links are provided with groove parts to avoid an interference with the first and second driving axles.

7. (withdrawn) The transporting apparatus according to claim 1, wherein outside ends of the driving links combined to the first and second driving axles at inside ends thereof, are connected with two pairs of transporting links, and the two pairs of transporting links are connected to two transporting tables, respectively.

8. (withdrawn) The transporting apparatus according to claim 1, wherein the driving links have a three-tiered structure, so that two transporting tables are different in height and alternately reciprocated.

9. (withdrawn) The transporting apparatus according to claim 8, wherein the driving links comprise:
first and third driving links symmetrically combined to the first driving axle; and
second and fourth driving links combined to the second driving axle, being placed up and down relative to the first and third driving links, respectively, to avoid an interference with each other.

10. (original) The transporting apparatus according to claim 1, wherein the links are connected to the first and second driving axles, and the first and second driving axles are different in height to prevent the links connected thereto from interfering with each other.

11. (original) The transporting apparatus according to claim 1, wherein the pivots allow the first and second driving axles to rotate in opposite directions.

12. (currently amended) The transporting apparatus according to claim 1, wherein the driving links are symmetrically rotated according to a rotation of the first and second driving axles.

13. (cancelled)

14. (currently amended) The transporting apparatus according to claim ~~43~~1, wherein one of the first and second driving axles is indirectly driven by the first motor.

15. (currently amended) The transporting apparatus according to claim ~~43~~1, wherein the supporting shaft and one of the first and second driving axles are provided concentrically.

16. (currently amended) The transporting apparatus according to claim ~~43~~1, wherein the driving part comprises:
a feedthrough and a bellows to make the driving part vacuum.

17. (withdrawn) A transporting apparatus, comprising:
a supporting part;
first and second driving axles rotatably supported by the supporting part;
a plurality of driving links respectively combined to the first and second driving axles;
a plurality of transporting links rotatably connected to the driving links; and
first and second transporting tables rotatably connected to the transporting links by pivots to reciprocate by a cooperation of the driving links and the transporting links, the first and second driving axles being aligned in a reciprocating direction of the first and second transporting tables.

18. (withdrawn) The transporting apparatus according to claim 17, wherein the transporting links comprise:

first and second transporting links rotatably connected to the first and second driving links; and

third and fourth transporting links rotatably connected to the second transporting table, the third and fourth transporting links and the second transporting table being placed opposite of

the first and second transporting and the first transporting table.

19. (withdrawn) The transporting apparatus according to claim 18, wherein outside ends of the driving links combined to the first and second driving axles at inside ends thereof, are connected with the first, second, third and fourth transporting links, and the first and second and the third and fourth transporting links are connected to the first and second transporting tables, respectively, enhancing transport efficiency.

20. (withdrawn) The transporting apparatus according to claim 18, wherein the pivots are provided to connect the first, second, third, and fourth transporting links with the first and second transporting tables, and are aligned in the reciprocating direction of the first and second transporting tables.

21. (withdrawn) The transporting apparatus according to claim 17, wherein the driving links comprise:

first and third driving links provided as a single body and symmetrically combined to the first driving axle; and

second and fourth driving links combined to the second driving axle, being placed up and down relative to the first and third driving links, respectively, to avoid an interference with each other.

22. (withdrawn) The transporting apparatus according to claim 21, wherein the first, second, third, and fourth driving links have a three-tiered structure, so that the first and second transporting tables are different in height to avoid an interference with each other and alternately reciprocate.

23. (withdrawn) The transporting apparatus according to claim 21, wherein the first, second, third, and fourth driving links are rotatably connected with the first, fourth, second and third transporting links, respectively.

24. (withdrawn) The transporting apparatus according to claim 21, wherein the first, third, and fourth driving links are provided with groove parts to avoid an interference with the first and second driving axles when the first, third, and fourth driving links are aligned in a reciprocating direction.

25. (cancelled)